

JC17 Rec'd PCT/PTO 10 JUN 2005

**Amendments to the Claims:**

This listing of claims will replace all prior versions and listings of claims in the application:

**Listing of Claims:**

1. (Currently amended) A protective cover (11) for motor vehicles, motor vehicle parts, machines or the like, which is adapted to the outer overall shape or the shape of individual parts of an object (12) to be protected and the edges of which are held on the object (12) to be protected, characterized in that a pocket (26) with at least one enclosed, flat strip-shaped holding element (24) is in each case provided along the at least one edge of the protective cover (11) which is assigned to a body edge (22, 25), which element in a holding position (37) acts under prestress on the body edge (22, 25) of the object (12) to be protected.
2. (Currently amended) The protective cover as claimed in claim 1, characterized in that the body edge (22, 25) of the object (12) to be protected is designed as a wheel arch (22) and/or engine hood edge (25) close to the windshield.
3. (Currently amended) The protective cover as claimed in claim 1 or 2, characterized in that the holding element (24) is larger in its width than a folded-over edge (35) of the body edge (22, 25).
4. (Currently amended) The protective cover as claimed in ~~one of the preceding claims~~ claim 1, characterized in that the flat strip-shaped holding element (24) has a radius of curvature which is designed to be larger than the radius or course of curvature of a body edge (22, 25).

5. (Currently amended) The protective cover as claimed in ~~one of the preceding claims~~ claim 1, characterized in that, to increase the holding force of the holding element (24) on the body edge (22, 25), the difference between the radius of curvature of the holding element (24) and that of the course of curvature of the body edge (22, 25) is increased.

6. (Currently amended) The protective cover as claimed in ~~one of the preceding claims~~ claim 1, characterized in that the holding element (24) is a part produced by punching, milling, injection molding, deep drawing, extrusion or calendering.

7. (Currently amended) The protective cover as claimed in ~~one of the preceding claims~~ claim 1, characterized in that the holding element (24) is formed from plastic, sheet metal, paperboard, cardboard, a composite material made of the abovementioned materials with and without fibers, fabric insert or fabric reinforcements.

8. (Currently amended) The protective cover as claimed in ~~one of the preceding claims~~ claim 1, characterized in that the holding element (24) is formed from a flat rectangular cross section and has flexible properties.

Claim 9 (Canceled).

10. (Currently amended) The protective cover as claimed in ~~one of the preceding claims~~ claim 1, characterized in that the holding element (24) is in a rest position inserted at least partly; ~~preferably or~~ completely into a pocket (26), which is formed from a material for the protective cover (11).

11. (Currently amended) The protective cover as claimed in ~~one of the preceding claims~~ claim 1, characterized in that the pocket (26) is formed from one or two layers (51, 52) and the layer or layers (51, 52) ~~can be~~ are connected by sewing, welding, or bonding after insertion of the holding element (24).

12. (Currently amended) The protective cover as claimed in ~~one of the preceding claims~~ claim 1, characterized in that a free inner space of the pocket (26) is designed to be slightly larger than the cross section of the flat strip-shaped holding element (24).

13. (Currently amended) The protective cover as claimed in ~~one of the preceding claims~~ claim 1, characterized in that the holding element (24) is of two-part or multi-part design.

14. (Currently amended) The protective cover as claimed in claim 13, characterized in that separating lines (43) formed between the holding elements (24) are provided at regular spacings in the case of a holding element (24) consisting of a number of portions (41, 42).

15. (Currently amended) The protective cover as claimed in claim 13, characterized in that a separating line (43) is provided at the apex of the body edge (22, 25) in the case of a holding element (24) consisting of a first and a further portion (41, 42).

16. (Currently amended) The protective cover as claimed in ~~claims~~ claim 13 ~~to 15~~, characterized in that each portion (41, 42) for forming a holding element (24) is inserted into a separate pocket (26).

17. (Currently amended) The protective cover as claimed in ~~claims~~ claim 13 ~~to 16~~, characterized in that each portion (41, 42) of the holding element (24) is inserted into a common pocket (26) and a seam (56) is provided in the region of the separating line (43) by sewing, bonding or welding for separate arrangement of the portions (41, 42) in the pocket (26).

18. (Currently amended) The protective cover as claimed in ~~claims~~ claim 13 ~~to 16~~, characterized in that the portions (41, 42) of the holding element (24) are arranged in relation to one another by a positive, non-positive and/or material connection before the insertion of the at least two-part holding element (24) into a common pocket (26).

19. (Currently amended) The protective cover as claimed in ~~claims~~ claim 13 ~~to 18~~, characterized in that the portions (41, 42) can be interconnected by sewing, welding, bonding or by a plug-type connection.

Claim 20 (Canceled).

21. (Currently amended) The protective cover as claimed in ~~claims~~ claim 13 ~~to 20~~, characterized in that a reinforcing strip (46), ~~preferably~~ is made of fabric, or fibrous material ~~or the like~~, and is applied on one side or both sides over each separating line (43) of the portions (41, 42) of the holding element (24).

22. (Currently amended) The protective cover as claimed in ~~one of the preceding claims~~ claim 1, characterized in that the pockets (26) with inserted holding element (24) or holding elements (24) ~~can be~~ are arranged on wheel arch coverings (21) adjacent to the body edge (22, 25) by sewing, welding, or bonding.